



132-S-900.7

(Specialist-IP Telephony Design Elective Exam)

Total Questions: 76

Last Updated: Apr 14, 2009

Document version: 8.27.11

Thanks for purchasing techXams' Study Guide,

techXams' 132-S-900.7 study guide is a comprehensive compilation of questions and answers that have been developed by our team of certified professionals. In order to prepare for the actual exam, all you need is to study the content of this guide. An average of approximately 10 to 20 hours should be spent to study this guide and you will surely pass your exam. It's our guarantee.

Disclaimer

Neither this guide nor any material in this guide is sponsored, endorsed or affiliated with any of the respective vendor. All trademarks are properties of their respective owners.

Guarantee

If you study this guide properly and still unable to pass the exam, please send us a scanned copy of your official score at: refund@techeXams.ws. We will happily reimburse the cost of this study guide or send you an exchange of study guide of your choice free of cost.

Feedback

If you find any possible improvement, then please do let us know. We are always interested in improving the quality of this product. Feedback can be send at: feedback@techeXams.ws

Copyright

techXams holds the copyright of this material. techXams grants you a limited license to view and study this material, either for personal or commercial use. Unauthorized reproduction or distribution of this material, or any portion thereof, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under law.

Question: 1

A customer has two sites connected over a 512k serial WAN link. There are 40 employees at the main site and 20 employees at the remote site. Since the server bank and all trunks terminate at the main location, the customer has concerns about the bandwidth over the WAN link. They request a network assessment. Which two design considerations are pertinent to the bandwidth on the WAN link? (Choose two.)

- A. VLAN capable Ethernet switch
- B. telecommuters using IP Softphone to access network resources
- C. number of voice calls going through the WAN link during peak time
- D. graphic-based programs used on the network between the two sites

Answer: C, D

Question: 2

Within an S8500 Server, 25 IP telephony endpoints are simultaneously connected to 10 digital sets, 10 IP sets, and 5 CO trunks. How many DSPs are in use if G.711 is incorporated?

- A. 15
- B. 25
- C. 30
- D. 50

Answer: A

Question: 3

An Avaya customer with a large contact center is IP enabling their S87xx and will allow 25 users to work from home via IP Agent in the Telecommuter mode. What is the minimum hardware required in the S87xx to provide this application?

- A. one CLAN board only
- B. one Media Processor board only
- C. one CLAN and one Media Processor board
- D. no hardware is required, only software.

Answer: A

Question: 4

What needs to be considered at an Enterprise Survivability Server (ESS) location when implementing an agent recording solution?

- A. H.323 trunks
- B. locally sourced announcements
- C. Application Enablement Services (AES)

2

D. Separation of Bearer and Signaling (SBS)

Question: 5

You are developing S87xx sites. The client has 1.5 Mbps. In addition to the client's traffic, you need to provide access to the Internet. How much traffic will add to the WAN traffic?

- A. 1.5 Mbps
- B. 275 Kbps
- C. 1650 Kbps
- D. 4675 Kbps

Answer: C

Question: 6

Which two recommendations properly with dynamic IP telephony?

- A. DHCP Site Specific
- B. DHCP Site Specific
- C. using Fast Spanning Tree
- D. turning off Spanning Tree

Answer: C

Question: 7

Which of the following is a right to use?

- A. Right to use
- B. Right to use
- C. Right to use
- D. Right to Use

Answer: B, C

Answer: C

132-S-900.7 Demo Exam