



920-221

(Nortel Converged Campus ERS Installation & Configuration)

Total Questions: 59

Last Updated: Dec 08, 2008

Document version: 8.27.11

Thanks for purchasing techXams' Study Guide,

techXams' 920-221 study guide is a comprehensive compilation of questions and answers that have been developed by our team of certified professionals. In order to prepare for the actual exam, all you need is to study the content of this guide. An average of approximately 10 to 20 hours should be spent to study this guide and you will surely pass your exam. It's our guarantee.

Disclaimer

Neither this guide nor any material in this guide is sponsored, endorsed or affiliated with any of the respective vendor. All trademarks are properties of their respective owners.

Guarantee

If you study this guide properly and still unable to pass the exam, please send us a scanned copy of your official score at: refund@techeXams.ws. We will happily reimburse the cost of this study guide or send you an exchange of study guide of your choice free of cost.

Feedback

If you find any possible improvement, then please do let us know. We are always interested in improving the quality of this product. Feedback can be send at: feedback@techeXams.ws

Copyright

techXams holds the copyright of this material. techXams grants you a limited license to view and study this material, either for personal or commercial use. Unauthorized reproduction or distribution of this material, or any portion thereof, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under law.

Question: 1

You are using the Nortel Network Command Line Interface (NNCLI) to modify a VLAN or a port. Which NNCLI command mode are you using?

- A. Global Configuration Mode
- B. Interface Configuration Mode
- C. Privileged EXEC Mode
- D. Router Configuration Mode

Answer: B

Question: 2

If you do not know the IP address of an Ethernet Routing Switch 5510, how can you upload code?

- A. Use Telnet.
- B. Use Console Access.
- C. Use the Web browser.
- D. Use the Java Device Manager.

Answer: B

Question: 3

A customer would like to configure an IP address for an existing VLAN on an Ethernet Routing Switch 5510. You use the following Command Line Interface (CLI) command sequence: From the initial CLI prompt, enter privilege mode, enter config mode, enter config-if mode for the VLAN interface. Enter the command, "ip address". What information do you enter next?

- A. Enter the appropriate IP address of the backup CPU.
- B. Enter the appropriate IP address and subnet mask in dotted decimal notation.
- C. Enter the appropriate IP address for the out-of-band management port.
- D. Enter the appropriate IP address for the in-band management port.

Answer: B

Question: 4

You can use the User Interface (UI) button on the Ethernet Routing Switch 5500 to temporarily reset a switch to the default IP address. Which two statements are true about the default IP address set via the UI button? (Choose two.)

- A. The default IP address overrides the IP address currently in use by the switch stack.
- B. The default IP address overwrites the onfigured IP address settings that are set via console, Command Line Interface (CLI), or Web.

2

- C. The default IP address changes if there is a change in the state of the switch, such as if the switch joins or leaves a stack.
- D. The default IP address is saved in NVRAM across resets of the switch/stack.

Answer: A, C

Question: 5

Which two statements are true?

(Choose two.)

- A. PoE requires a switch to be configured with a PoE profile.
- B. PoE enables a switch to power a device.
- C. PoE provides a way to power a device over a network.
- D. PoE is used to power a switch.

Answer: A, D

Question: 6

You are installing an environmental and cooling system. Which is your first step?

Read that
 Routing Switch.

- A. Follow Electrical Code requirements.
- B. Mount switch sensors.
- C. Provide a console connection.
- D. Check the software version.

Answer: A

920-221 Demo Exam