



920-462

(Ethernet Switching)

Total Questions: 56

Last Updated: Jan 01, 2009

Document version: 8.27.11

Thanks for purchasing techXams' Study Guide,

techXams' 920-462 study guide is a comprehensive compilation of questions and answers that have been developed by our team of certified professionals. In order to prepare for the actual exam, all you need is to study the content of this guide. An average of approximately 10 to 20 hours should be spent to study this guide and you will surely pass your exam. It's our guarantee.

Disclaimer

Neither this guide nor any material in this guide is sponsored, endorsed or affiliated with any of the respective vendor. All trademarks are properties of their respective owners.

Guarantee

If you study this guide properly and still unable to pass the exam, please send us a scanned copy of your official score at: refund@techeXams.ws. We will happily reimburse the cost of this study guide or send you an exchange of study guide of your choice free of cost.

Feedback

If you find any possible improvement, then please do let us know. We are always interested in improving the quality of this product. Feedback can be send at: feedback@techeXams.ws

Copyright

techXams holds the copyright of this material. techXams grants you a limited license to view and study this material, either for personal or commercial use. Unauthorized reproduction or distribution of this material, or any portion thereof, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under law.

Question: 1

A stock trading firm has just installed a server for online trading. Once a customer requests a stock trade via the Internet, the server must interlace with the Stock Exchange via their Passport network, using a protocol which supports authentication, encryption and integrity assurance. Which supported protocol is appropriate for the Passport configuration?

- A. RADIUS Client
- B. RADIUS Server
- C. Secure Shell (SSH) Client
- D. Secure Shell (SSH) Server

Answer: D

Question: 2

A customer with a Passport 8300 switch is configuring Remote Access Dial-In User Services (RADIUS) to provide a high degree of security against unauthorized access to the switch. They configured ten RADIUS servers on the client (Passport 8300 switch). What will happen if an authentication request is rejected by the first of five RADIUS servers configured on the switch?

- A. Local authentication is made on the switch itself.
- B. No local authentication is made on the switch itself.
- C. If the first server is unavailable, the Passport 8300 tries the second and so on until it establishes a successful connection.
- D. If the first server rejects the authentication request, the Passport 8300 tries the second and so on until it establishes a successful connection. If all of them reject the request, local authentication is made on the switch itself.

Answer: B

Question: 3

A customer wants to configure SNMPv3 on the Passport 8300 switch. SNMPv3 requires a loadable module for the encryption libraries. What does this module contain and how must you modify the config file to load this module?

- A. The module contains key code and the string `load-module KEY/flash/<key_filename>`; must be inserted in config file.
- B. The module contains SSH algorithm and the string `load-module SSH/flash/<ssh_filename>`; must be inserted in config file.

2

C. The module contains DES algorithm and the string load-module DES/flash/<des_filename> must be inserted in config file. The module contains DES algorithm and the string load-module DES/flash/<des_filename> must be inserted in config file
 D. The module contains license algorithm and the string license-module DES/flash/<des_filename> must be inserted in config file

Answer: C

Question: 4

Instead of using IP command will enable RIP on P
 vlan 2 ip rip enable
 configuration on P

- A. config vlan 2 ip rip
- B. config vlan 2 ip rip
- C. config vlan 2 ip rip
- D. config vlan 2 ip rip

following
 RTM for RIP: config
 this type of PIP

Answer: D

Question: 5

A customer wants
 connected to the B
 RIP. Assuming that
 file identifies the r

- A. ethernet 2/7 ip cre
 ip rip enable
- B. ethernet 2/7 ip cre
 ip rip enable

VLAN 2 and VLAN 3
 a Brouter port with
 00A configuration

et 2/7 ip rip enable ip
 et 2/7 ip rip enable

Answer: A

920-462 Demo Exam