



920-464

(Nortel Converged Campus ERS Rls. 4.x/5.x Advanced Configuration & Maintenance)

Total Questions: 59

Last Updated: Apr 09, 2009

Document version: 8.27.11

Thanks for purchasing techXams' Study Guide,

techXams' 920-464 study guide is a comprehensive compilation of questions and answers that have been developed by our team of certified professionals. In order to prepare for the actual exam, all you need is to study the content of this guide. An average of approximately 10 to 20 hours should be spent to study this guide and you will surely pass your exam. It's our guarantee.

Disclaimer

Neither this guide nor any material in this guide is sponsored, endorsed or affiliated with any of the respective vendor. All trademarks are properties of their respective owners.

Guarantee

If you study this guide properly and still unable to pass the exam, please send us a scanned copy of your official score at: refund@techeXams.ws. We will happily reimburse the cost of this study guide or send you an exchange of study guide of your choice free of cost.

Feedback

If you find any possible improvement, then please do let us know. We are always interested in improving the quality of this product. Feedback can be send at: feedback@techeXams.ws

Copyright

techXams holds the copyright of this material. techXams grants you a limited license to view and study this material, either for personal or commercial use. Unauthorized reproduction or distribution of this material, or any portion thereof, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under law.

Question: 1

The following commands complete a configuration for traffic filtering on an Ethernet Routing Switch (ERS) 8600 E module:

```
<missing command> config ip traffic-filter global-set 1 add-filter 1 config ethernet 1/2 enable-diffserv true config ethernet 1/2 ip traffic-filter create config ethernet 1/2 ip traffic-filter add set 1 config ethernet 1/2 ip traffic-filter default-action forward config ethernet 1/2 ip traffic-filter enable
```

Step one is missing.

Which command is missing?

- A. config ip traffic-filter filter 1 forward equal
- B. config ip traffic-filter traffic-profile 1 info
- C. config ip traffic-filter global-set 1 create name gfilter1
- D. config ip traffic-filter create global src-ip 10.1.1.2/30 dst-ip 172.1.1.29/30 id 1

Answer: C

Question: 2

Simple Loop Prevention Protocol (SLPP) provides active protection against Layer 2 network loops on a per-VLAN basis. For the SLPP Tx Process, the network administrator decides on which VLANs to enable SLPP. The hello packets are then replicated out all ports that are members of the SLPP-enabled VLAN.

A = InterSwitch Trunk (IST) B = Split MultiLink Trunk (SMLT) #1 ERS 8600 #2 ERS 8600 #3 ERS 4500 When setting up the SLPP Rx Process which configuration role is setup on ERS #1?

- A. The ERS #1 Rx Process is enabled on all SMLT VLANs to monitor for ERS #3 SLPP packets.
- B. The ERS #1 Rx Process is enabled on port 3/1 and IST ports for ERS #2 SLPP packets.
- C. The ERS #1 Rx Process is enabled on all SMLT VLANs to monitor for ERS #2 SLPP packets.
- D. The ERS #1 Rx Process is enabled on port 3/1 to monitor for ERS #2 SLPP packets.

Answer: D

Question: 3

The upgrade of an Ethernet Routing Switch (ERS) 8300 to Rls. 4.1 was unsuccessfully installed and you must resolve the issue. The switch is out of network service. After you perform a power-on reset of the chassis it is running Rls. 4.1; however, the chassis modules have the following light indications:

Slot 1 8308XLOnline - yellow Slot 2 8348GTX Online - yellow Slot 5 8394Sf Master - green Slot 6 8394SF Master - flashing green

The results of the dir command indicate that the files p83a4100.img and p83b4100.img are present on flash on both CPUs along with the older Rls. 4.0 files. The results of the choices command indicate that the primary image file is specified as /flash/p83a4100.img and the secondary image /flash/p83a4000.img.

2

What is the most feasible cause of the unsuccessful upgrade?

- A. The ERS 8300 p831-4100 image file should be hosted on the primary image server.
- B. You can not upgrade from a 4.x to a 5.x image.
- C. The primary image server is not reachable.
- D. The I/O Module is not installed.

Answer: D

Question: 4

When incorporating (ERS) 8600 switches into a network, the ping-snoop feature is not working. The ping-snoop feature is not working. How does the ping-snoop feature work?

- A. Ping-snoop looks for the destination IP address in the ping-snoop command.
- B. Ping-snoop looks for the destination IP address in the ping-snoop command.
- C. Ping-snoop identifies the destination IP address in the ping-snoop command.
- D. Ping-snoop identifies the destination IP address in the ping-snoop command.

Answer: C

Question: 5

You have created a traffic filter on a switch with the following command: `config ip traffic-filter filter 3 action mode deny`. Which of the following commands will you use to apply the traffic filter to port 1/2?

- A. `config ip traffic-filter filter 3 action mode deny`
- B. `config ip traffic-filter filter 3 action mode deny`
- C. `config ip traffic-filter filter 3 action mode deny`
- D. `config ip traffic-filter filter 3 action mode deny`

Answer: B

920-464 Demo Exam