



920-471

(Nortel Converged Office for CS 1000 Rls. 5.x Configuration & Networking)

Total Questions: 62

Last Updated: Jun 20, 2009

Document version: 8.27.11

Thanks for purchasing techXams' Study Guide,

techXams' 920-471 study guide is a comprehensive compilation of questions and answers that have been developed by our team of certified professionals. In order to prepare for the actual exam, all you need is to study the content of this guide. An average of approximately 10 to 20 hours should be spent to study this guide and you will surely pass your exam. It's our guarantee.

Disclaimer

Neither this guide nor any material in this guide is sponsored, endorsed or affiliated with any of the respective vendor. All trademarks are properties of their respective owners.

Guarantee

If you study this guide properly and still unable to pass the exam, please send us a scanned copy of your official score at: refund@techeXams.ws. We will happily reimburse the cost of this study guide or send you an exchange of study guide of your choice free of cost.

Feedback

If you find any possible improvement, then please do let us know. We are always interested in improving the quality of this product. Feedback can be send at: feedback@techeXams.ws

Copyright

techXams holds the copyright of this material. techXams grants you a limited license to view and study this material, either for personal or commercial use. Unauthorized reproduction or distribution of this material, or any portion thereof, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under law.

Question: 1

A customer has an IP Peer Network and has made changes to the dialing plan in the Network Routing Service. Which Database Action option lets you activate changes and run tests without making the changes permanent?

- A. Cutover
- B. Commit
- C. Rollback
- D. Reset and Test

Answer: A

Question: 2

The customer recently implemented IP Peer Networking in a Communication Server 1000 Rls. 5.0 network. The customer now wants to deploy the Geographic Redundancy feature. Which Network Routing Service element must be configured to support Geographic Redundancy?

- A. Branch Office
- B. Collaborative Server
- C. Emergency Services
- D. Network Connection Service

Answer: D

Question: 3

A customer has IP Peer network using only the SIP protocol. Signaling Server 1 hosts the Primary NRS. The customer wants to add an Alternate NRS using Signaling Server 2, which resides at a remote site. Considering the company requirements, which step is required?

- A. Change NRS role of Signaling Server 2 to Active.
- B. Change NRS role of Signaling Server 2 to Alternate.
- C. Change the SIP URI Mapping to Alternate for all nodes.
- D. Change the ENL/DIS switch on Signaling Server 1 to Alternate.

Answer: B

Question: 4

You are configuring the Network Routing Service for an H.323 network. Which step is mandatory for all IP Peer Networking scenarios?

- A. Add a Service Domain
- B. Add a Collaborative Server
- C. Implement Geographic Redundancy
- D. Configure the Network Connection Server

Answer: A

Question: 5

Which Network Routing Service option lets you view the last database synchronization for the Alternate NRS?

- A. Tools
- B. Reports
- C. Configuration
- D. Administration

Answer: B

Question: 6

You have received a work order to add a new endpoint to the Network Routing Service database. Which database schema or view would you use for administrator modifications?

- A. Active
- B. Standby
- C. Passthru
- D. Collaborative

Answer: B

Question: 7

You are defining generic settings for the NRS Server. Which is the correct entry or definition for the NRS Server Host name?

- A. Node ID address of the SIP Proxy
- B. ELAN IP address of the Call Server
- C. TLAN IP address of the Primary NRS

D. Alias of connected host Signaling Server

Answer: D

Question: 8

During a planned work on a Communication Server for IP telephones were unable to connect to them. Which data on the Signaling Server will you check?

- A. Re-boot the Alternate Signaling Server
- B. Verify that the Alternate Signaling Server is up
- C. Verify that the Signaling Server is up
- D. Verify that the Alternate Signaling Server is up

Signaling Server on the alternate Signaling Server, some IP telephones are unable to connect to them. Which data on the Signaling Server will you check?

- A. Verify that the Signaling Server is up
- B. Verify that the Alternate Signaling Server is up
- C. Verify that the Signaling Server is up
- D. Verify that the Alternate Signaling Server is up

Answer: D

Question: 9

You are using Element Manager for Peer Networking. What is the first step in configuring a VxWorks device?

- A. Call Server
- B. Hardware watchdog
- C. Network Connection
- D. Basic Input Output

When you are implementing IP Peer Networking, what is the first step in configuring a VxWorks device?

Answer: A

Question: 10

Signaling Server

- A. Call Server
- B. NRS Manager
- C. Branch Office
- D. Media Gateway

Answer: B