



HH0-200

(Certified Modular Integration Specialist Exam)

Total Questions: 88

Last Updated: Feb 26, 2008

Document version: 8.27.11

Thanks for purchasing techXams' Study Guide,

techXams' HH0-200 study guide is a comprehensive compilation of questions and answers that have been developed by our team of certified professionals. In order to prepare for the actual exam, all you need is to study the content of this guide. An average of approximately 10 to 20 hours should be spent to study this guide and you will surely pass your exam. It's our guarantee.

Disclaimer

Neither this guide nor any material in this guide is sponsored, endorsed or affiliated with any of the respective vendor. All trademarks are properties of their respective owners.

Guarantee

If you study this guide properly and still unable to pass the exam, please send us a scanned copy of your official score at: refund@techeXams.ws. We will happily reimburse the cost of this study guide or send you an exchange of study guide of your choice free of cost.

Feedback

If you find any possible improvement, then please do let us know. We are always interested in improving the quality of this product. Feedback can be send at: feedback@techeXams.ws

Copyright

techXams holds the copyright of this material. techXams grants you a limited license to view and study this material, either for personal or commercial use. Unauthorized reproduction or distribution of this material, or any portion thereof, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under law.

Question: 1

You have assembled and installed a Hitachi Thunder 9570V?subsystemRK and a RKA into a 19 inch rack. The system parameters have also been configured. The customer now needs to use port 0A in order to connect HP-UX with a LUN 0 and Solaris with a LUN 0 on the same port. Which two will enable this configuration? (Choose two.)

- A. install the LUN SECURITY license
- B. create two host groups on port 0A
- C. install the LUN-MANAGEMENT license
- D. configure port 0A to work in HP-UX mode

Answer: B, C

Question: 2

What is the operational humidity requirement at a site when installing a Hitachi Thunder 9500V?Series subsystem?

- A. 5% to 90%
- B. 8% to 80%
- C. 10% to 75%
- D. 10% to 90%

Answer: B

Question: 3

Which statement is true about cache slots on the Hitachi Thunder 9500V?Series subsystem?

- A. Each controller has two cache slots and each slot can hold 1GB DIMMS for a maximum of 2GB per controller.
- B. Each controller has two cache slots and each slot can hold 512MB or 1GB DIMMS for a maximum of 1GB or 2GB per controller.
- C. Each controller has four cache slots and each slot can hold 512MB or 1GB DIMMS for a maximum of 2 GB or 4GB per controller.
- D. Each controller has four cache slots and each slot can hold 256MB or 512MB DIMMS for a maximum of 1 GB or 2 GB per controller.

Answer: B

Question: 4

Click on the "letter" representing the LED that indicates a failure in the controller.

Answer: Pending

Question: 5

Which component does not support the 9570V? Series subsystems

- A. PDB
- B. ENC unit
- C. Controller unit
- D. AC Power Unit

Hitachi Thunder

Answer: B

Question: 6

You are connected to the Hitachi Manager GUI. You have one spare disk. Give the following commands:

- A. select Settings->Storage->Spare
 - B. select Settings->Storage->Disk
 - C. select the Logical Disk
 - D. select Settings->Storage->Logical Disk
 - E. select the disk to be used as a spare
 - F. select the Spare Disk
- A. B, F, E
 B. B, F, G
 C. D, C, E

Hitachi?Resource you want to set up

Answer: B

HHO-200 Demo Exam