



## **HP0-436**

**(Open VMS v7 Network Administration)**

Total Questions: 126

Last Updated: Nov 06, 2007

Document version: 8.27.11

Thanks for purchasing techXams' Study Guide,

techXams' HP0-436 study guide is a comprehensive compilation of questions and answers that have been developed by our team of certified professionals. In order to prepare for the actual exam, all you need is to study the content of this guide. An average of approximately 10 to 20 hours should be spent to study this guide and you will surely pass your exam. It's our guarantee.

### Disclaimer

Neither this guide nor any material in this guide is sponsored, endorsed or affiliated with any of the respective vendor. All trademarks are properties of their respective owners.

### Guarantee

If you study this guide properly and still unable to pass the exam, please send us a scanned copy of your official score at: [refund@techeXams.ws](mailto:refund@techeXams.ws). We will happily reimburse the cost of this study guide or send you an exchange of study guide of your choice free of cost.

### Feedback

If you find any possible improvement, then please do let us know. We are always interested in improving the quality of this product. Feedback can be send at: [feedback@techeXams.ws](mailto:feedback@techeXams.ws)

### Copyright

techXams holds the copyright of this material. techXams grants you a limited license to view and study this material, either for personal or commercial use. Unauthorized reproduction or distribution of this material, or any portion thereof, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under law.

## Question: 1

**What do you do to preserve site-specific parameter settings and commands for a specific TCPIP service?**

- A. Edit SYS\$SYSTARTUP:TCPIP\$SYSTARTUP.COM
- B. Edit SYS\$SYSTEM:TCPIP\$SYSTARTUP.COM
- C. Create files of the form SYS\$SYSTEM:TCPIP\$service\_SYSTARTUP.COM
- D. Create files of the form SYS\$STARTUP:TCPIP\$service\_SYSTARTUP.COM

Answer: D

## Question: 2

**What driver does SCA use to run cluster traffic on NICs?**

- A. SYS\$NIDRIVER.EXE
- B. SYS\$PEDRIVER.EXE
- C. SYS\$EWDRIWER.EXE
- D. SYS\$PADRIVER.EXE

Answer: B

## Question: 3

**Which command is a prerequisite to using sysconfig -q socket?**

- A. SYSCONFIG ENABLE
- B. @TCPIP\$DEFINE\_COMMANDS
- C. SET PROCESS/PRIVILEGE = ALL
- D. @TCPIP\$DEFINE\_SYSCONFIG

Answer: B

## Question: 4

**After replacing a DECserver, you cannot connect to it using SET HOST/MOP. Using NCL, what needs to be modified?**

- A. MOP client address
- B. MOP circuit address
- C. MOP listener address
- D. MOP client node id

Answer: A

Question: 5

An OpenVMS system has a `node` statement in the BIND configuration file and a `node` statement in the BIND database?

- A. transfer-out
- B. query-source
- C. allow-transfer
- D. allow-update

...ement in the BIND  
...the same

Answer: C

Question: 6

How do you determine the status of the TCPIP stack?

- A. TCPIP TRACE
- B. netstat -m
- C. TCPIP SHOW PR
- D. TCPIP SHOW TC

Answer: C

Question: 7

How do you determine the status of the cluster?

- A. SHOW CLUSTER
- B. NCL> SHOW PR
- C. SDA> SHOW LA
- D. SHOW CLUSTER

...n: C

# HP0-436 Demo Exam